

BEST AVAILABLE COPY

15oct04 11:29:45 User015070 Session D10468.1
Sub account: BALDS2.021APC-CSP

FILE JPCEMENT.DOC

ENGLISH ABSTRACTS FOR 2 JAPANESE PATENTS

SYSTEM:OS - DIALOG OneSearch

File 351:Derwent WPI 1963-2004/UD,UM &UP=200466

(c) 2004 Thomson Derwent

*File 351: For more current information, include File 331 in your search.

Enter HELP NEWS 331 for details.

File 345:Inpadoc/Fam.& Legal Stat 1968-2004/UD=200441

(c) 2004 EPO

File 347:JAPIO Nov 1976-2004/Jun(Updated 041004)

(c) 2004 JPO & JAPIO

*File 347: JAPIO data problems with year 2000 records are now fixed.

Alerts have been run. See HELP NEWS 347 for details.

Set	Items	Description
-----	-------	-------------

---	-----	-----
-----	-------	-------

?.exs

Executing TD687

10/7/1 (Item 1 from file: 351)

DIALOG(R)File 351:Derwent WPI

(c) 2004 Thomson Derwent. All rts. reserv.

007084035

WPI Acc No: 1987-084032/*198712*

Additive for extrusion moulded cement compsn. - comprises cellulose
deriv. and condensate of (alkyl)naphthalene sulphonic acid and/or
melamine-sulphonic acid with polyformaldehyde

Patent Assignee: SANYO CHEM IND LTD (SANN)

Number of Countries: 001 Number of Patents: 001

Patent Family:

Patent No	Kind	Date	Applicat No	Kind	Date	Week
JP 62036055	A	19870217	JP 85176237	A	19850809	198712 B

Priority Applications (No Type Date): JP 85176237 A 19850809

Patent Details:

Patent No	Kind	Lan	Pg	Main IPC	Filing Notes
JP 62036055	A		4		

Abstract (Basic): JP 62036055 A

Additive consists of water-soluble or water-dispersive cellulose
deriv. (90-50 wt.%) and condensate salt of (alkyl) naphthalene
sulphonic acid - formaldehyde and/or condensate salt of melamine
sulphonic acid - formaldehyde (10-50 wt.%).

Pref. 0.1-5 pts.wt. (0.2-2 pts.wt.%) are used per 100 pts.wt.
cement (e.g. mixt. of cement 100 pts.wt. fibrous material 2-40 pts.wt.
aggregate 0-40 pts.wt. and water 20-70 pts.wt.

USE/ADVANTAGE - The compsn. has high water-retentivity, and its slipperiness in press-out machine is increased. Cement prod. having fine surface appearance is obtd. Press-out moulded cement prod. is produced with high efficiency.

0/0

Derwent Class: A93; L02

International Patent Class (Additional): C04B-024/22